

☐ Inquiry ☐ Or	der	
NewGlassTechr	<u> </u>	Contact person:
Where progress never stops Tel: 003293955599 Fax: 003293955099 info@newglasstech.com http://newglasstech.com		Telephone:
		Quotation No.:
		Commission:
Type: SF 75 high thermally insulated aluminium system high thermally insulated aluminium system with solid timber cladding of all visible inside aluminium profiles (except bottom rail) Type of timber and finish:		
Opening direction: inwards folding outwards folding		
Number of panel: to the left to the right (Please draw a floor plan or a view sketch for better understanding)		
Dimensions: Width:	(Total unfolding)	Height: (incl. possible floor recession)
Colour: RAL 7016	RAL 9006 RAL 9007	RAL 9016 E6-EV1 Special colour Pre anodizing
Colour of hinges:	E6-EV1 powder RAL 901	11 RAL 9016 Special colour
Handle colour:	E6-EV1 powder RAL 901	11 RAL 9016 Special colour
Glazing:	Standard heat protection glass 2 x 4 without glass: prepared for Special glass:	
Floor connection:	with weathered bottom track with flush bottom track (height incl. floor recession)	
Locking of turn panel:	Standard (shoot bolt lock operated from inside only) Shoot bolt lock with PZ (operated from both sides) Roller latch + 2 x dead lock + HEWI push handle Anti-draft lock with mushroom head and 4 point locking, latch and profile cylinder (operable on both sides) Pull handle for turn panel, outward folding system other:	
Additional safety:	Twin-Lock WK2-Safety package	

Please enclose floor plan resp. view sketch and remarks (please use inside view)



