

# CONTRAFLAM® 30

## Fire resistant safety glass for interior application

### CLASSIFICATION

**EI** = Integrity +  
Insulation

Ability to withstand fire exposure without transmission of fire to the non-fire side as a result of the passage of flames, hot gases or significant conduction of heat, thereby causing ignition of the non-fire exposed surface or materials in contact, and provides a barrier to heat to protect people.

### PRODUCT FEATURES

Toughened safety glass

Intumescent Interlayer

Edge Sealant



### TECHNICAL SPECIFICATIONS

#### Fire resistance (EN 13501-2)

Reaction to fire (EN 13501-1)

Maximum Glass Size

Thickness tolerance

Length tolerance

Impact resistance (EN 12600)

UV stability (EN ISO 12543-4 point 6)

Application Conditions

CE certificate No. of conformity

Hazardous material contained

**EI 30**

A2-s1, d0

Variable, subject to glass make-up, framing material or glazed element type.

Consult with your Vetrotech representative.

+2/-1 mm

±2 mm

1 (B) 1 classification

In addition to the standard specifications: no formation of bubbles or yellowing after 2000 hours of exposure to radiation.

Avoid prolonged exposure to extreme temperatures. Exterior applications must be supplied as an IGU with Low-E or Solar Control coating. For more information consult your Vetrotech representative or refer to "Quality Guideline, Application Conditions".

0336-CPD-5064C/ID No.\* (you can obtain a DoP\*\* from your national sales office) - AoC-level 1

None

#### Nominal thickness

Glass size per thickness

Weight

Sound reduction  $R_w$  (EN 140-3)

Light transmission (EN 410)

Light reflection  $\rho_L$  (exterior/interior)

U value,  $W/m^2K$  (EN 673)

g value

Energy transmission  $\tau_E$

Energy reflection  $\rho_E$  (exterior/interior)

**16 mm**

≤ 1500 mm x 3000 mm

34 kg/m<sup>2</sup>

38 dB

86%

9%/9%

4,8

0,72

65%

7%/7%

**18 mm**

≤ 1800 mm x 3500 mm

39 kg/m<sup>2</sup>

40 dB

85%

9%/9%

4,8

0,70

63%

7%/7%

**22 mm**

≤ 2300 mm x 3800 mm

49 kg/m<sup>2</sup>

40 dB

84%

8%/8%

4,7

0,68

60%

7%/7%

\* ID No. = Identification number for the relevant manufacturing site

\*\* Declaration of Performances