

CONTRAFLAM® 60 Climaplus Horizontal

Fire resistant safety glass for interior and exterior application

CLASSIFICATION

EI = Integrity + Insulation

Ability to withstand fire exposure without transmission of fire to the non-fire side as a result of the passage of flames, hot gases or significant conduction of heat, thereby causing ignition of the non-fire exposed surface or materials in contact, and provides a barrier to heat to protect people.


PRODUCT FEATURES

Outer pane with low emission and/or solar control properties

Fire resistant safety glass CONTRAFLAM® 60, 30 mm

Spacer

Laminated safety glass



TECHNICAL SPECIFICATIONS

Fire resistance (EN 13501-2)

Reaction to fire (EN 13501-1)

Maximum Glass Size

Thickness tolerance

Length tolerance

UV stability (EN ISO 12543-4 point 6)

Application Conditions

CE certificate No. of conformity

Hazardous material contained

EI 60

B-s1, d2

Variable, subject to glass make-up, framing material or glazed element type. Consult with your Vetrotech representative.

±3 mm

±2 mm

In addition to the standard specifications: no formation of bubbles or yellowing after 2000 hours of exposure to radiation.

Avoid prolonged exposure to extreme temperatures. Exterior applications must be supplied as an IGU with Low-E or Solar Control coating. For more information consult your Vetrotech representative or refer to "Quality Guideline, Application Conditions".

0336-CPD-5064D/ID No.* (you can obtain a DoP** from your national sales office) - AoC-level 1

None

Nominal thickness

Outer pane

Spacer

Inner pane

Impact resistance (EN 12600) (outside/inside)

Weight

Sound reduction Rw (EN 140-3)

Light transmission (EN 410)

Light reflection ρL (outside/inside)

U value, W/m²K (EN 673) (0°/40°)

g value

Energy transmission τE

Energy reflection ρE (outside/inside)

50 mm

6 mm Planitherm Ultra N float

14 mm with Argon gas filling

CONTRAFLAM® 60, 30 mm

NPD***/1 (B) 1 classification

79 kg/m²

NPD***

72%

13%/12%

1,1 (1,6/1,4)

0,55

40%

25%/11%

50 mm

6 mm Planitherm Ultra N II toughened

14 mm with Argon gas filling

CONTRAFLAM® 60, 30 mm

1 (C) 2/1 (B) 1 classification

79 kg/m²

NPD***

72%

13%/12%

1,1 (1,6/1,4)

0,55

40%

25%/11%

* ID No. = Identification number for the relevant manufacturing site

** Declaration of Performances

*** NPD = No Performance Declared