

NewGlassTechnology |

☐ Inquiry ☐ Order	_
NewGlassTechnology Where progress never stops	Contact person: Telephone:
Tel: 003293955599 Fax: 003293955099 info@newglasstech.com	Quotation No.:
http://newglasstech.com	Commission:
Type: SF 55 thermally insulated aluminium system thermally insulated aluminium system with solid timber cladding of all visible inside aluminium profiles (except bottom rail) Type of timber and finish:	
Opening direction: inwards opening outwards opening	
Parking bay: Typ 1 Typ 2 Typ 3	Special solution
Number of panel: to the left to the right (Please draw a floor plan or a view sketch for better understanding)	
Dimensions: Width: (Total unfolding)	Height: (incl. possible floor recession)
Colour: RAL 7016 RAL 9006 RAL 9007 RAL 9016 E6-EV1 Special colour Pre anodizing	
Handle colour: E6-EV1 powder RAL 9011 RAL 9016 Special colour	
Glazing: Standard Insulated glass 2 x 4/20 cavity Ug 1.1 without glass: prepared for mm Special glass: (Please indicate exact designation)	
Ceiling connection: without overlay profile with overlay profile inside with overlay profile outside	
Ground connection: with floor sockets with flush bottom track (height incl. floor recession)	
Locking of turn panel: Standard (shoot bolt lock operated from inside only) Shoot bolt-lock with PZ (operated from both sides) Mortise door lock with PZ (operated from both sides) Roller latch + 2 x dead lock + HEWI push handle Anti-draft lock with mushroom-lock, latch and PZ (operated from both sides) other:	
	r, push handle, 2 x dead lock th PZ and handle at both sides ft to the right.

Please enclose floor plan resp. view sketch and remarks (please use inside view)



